

For bathroom, laundry and family rooms

U.L. Listed and C.S.A. Approved










Twin Blower Model 8700

For installation in kitchen cabinets on inside wall or outside wall. Also for duo-level installation in ceiling or soffit.

*For installation in cabinets; includes cabinet mounting kit and filter. Use Model 860 Three Speed Switch.

Model No.	Grille Finish	H.V.I. in sq Kitchen	uare	feet
8700 8720*	Anod. Alum.	100 100	185 185	250 250
8710 8730*	Copper Anod.	100	185 185	250 250

#8700-8710 \$39.50 #8720-8730 \$43.50




U.S. Pat. Nos. 2,300,504; 447,586; 519,112; 2,842,307; 2,856,836

Bathroom Fan Model 8810

Designed especially for Bathroom use where closed doors require a fan with high static pull. Discharges to outside through 4" diameter duct. Has adjustable bracket . no blocking from joists. Snap-in mounting. Moistureproof motor resists bathroom moisture. Use Model 862 60-Minute Time Switch.

	Model No.	Grille Finish	H.V.I. o in squ Kitchen	uare 1	feet
ı	8810	Anod. Alum	Not used	75	100




Motors Guaranteed for 5 Years

Bathroom Fan Model 8830 for Ceiling or Inside Wall

Designed especially for Bathroom use where closed doors require a fan with high static pulls. For all types of bathrooms. Less than 4" thin-fits in ceiling or between 2" x 4" studs. Discharges to outside through 3" dia. duct. Meets FHA requirements. Use Model 862 60-minute Time Switch.

Model		H.V.I. CERTIFIED			
No.	Finish	Kitchen	Bath	Other	
8830	Anod, Alum.	Not used	65	90	

List Price \$23.95



Vent-A-Lite® Model 8660

Exhaust Fan plus Light

Both for the cost of one combination unit. Blower is quiet — moves just the right amount of air — no drafts. It's Round — provides better lighting — Installs between 2 x 6 joists. Hinged lens for 100 watt bulb replacement. Overall depth below ceiling 2½". Includes 2 hanger bars. Discharges through 4" dia. duct.

Grille

Model

H.V.I. CERTIFIED



Motor is soring mounted for quiet operation



All ventilating fans which display the H.V.I. Label have been tested by the Texas Engineering Experiment Station at Texas A&M College, in accordance with the Standard Test Code, approved by H.V.I.

Home Ventilating Institute — Certified Ratings

The room rating — by square foot method has been applied in accordance with F.H.A. and H.V.I. specifications. Performance of the particular fan at appropriate static pressure points is determined by the aforementioned Independent test facility.

ROOM	AIR CHANGES PER HOUR
Kitchen Bathroom	15
Family, Laundry, or Recreation Room	6

Static	Pressure	e Poir	nts	_	
Connected			.10	inches	W.G.

Direct Discharge Wall Fans .03 inches W.G.

NUTONE VENTILATION ACCESSORIES

Model	Description	Price	Model	Description	Price	Model	Description
823 Reduce to 8" re 824 Transitir 90" ttr 834 Filter f 836 Eave ca termina 837 Flush V termina 838 Wall Ca	r with damper. Use with 8220 to adapt pund duct ion Elbow with damper. Use with 8220 for 10 3½ X 10" duct size for 8060-8200-8210-8220-8310 sp. Has weather louver. Use to te 3½ X 10" duct. Wall Cap. Has weather louver. Use to te 3¼ X 10" duct. Use to the 3¼ X 10" duct.	2.60 or 3.70 2.10 5.60	845 Roof up to 854 Filter 860 3-Spe 8700-881 3-Spe 862 60 Mi 8660, 874 314 X	ap with weather damper. For duct 10" square for 8170-8190-8490-8510 fans at Switch for 8170-8190-8310-8490-8570 at Switch. For 8060-8090. Institute Time Switch for use with 8810, 8830, 9200, 9280 and 9290 but 10" duct. 18" long.	8.50 2.30 510 and 6.25 6.25 Heaters. 8.80 2.60	885 Wall C4 4" roun 886 Transiti 887 7" roun 888 Flat Ell 889 3¼ X 1 890 7" roun 894 Transiti 8200-82	Description ap with weather louver. For use with did duct. ion — 7" round to 3¼" x 10" duct 18" long bow for 90" turn. For use with 3¼ X 10" du ow for 90" turn. For use with 3¼ X 10" du duct. Each section 24" long. 5 sections for on Elbow with damper. Use with 10 for 90" turn to 3¼ X 10" duct size
839 Elbow 840 Adjusta 841 Roof Ca	ate 314 X 10" duct. 90" turn. For use with 314 X 10" duct. sable Elbow for use with 4" round duct. ap for 4" diameter duct. For use with 8660, 8830, 9090, 9110, 9300, 9310 and 3260	4.95 3.30 2.00 4.75	876 Damp 877 Trans	lation Kit for installing 8700-8710 in er section 7" long. For use with 34 ition 6" round to 344 X 10" for 8700-8710	4 X 10" duct. 3.85	897 Transiti 898 Right R 899 Left Re	on Elbow 90°. 4 X 12" to 3¼ X 10"

lode	1 Description	Price
885	Wall Cap with weather louver. For use with 4" round duct.	3.10
886	Transition — 7" round to 3¼" x 10"	3.50
887	7" round duct 18" long	1.80
888	Flat Elbow for 90° turn. For use with 3¼ X 10" du	ct.4.00
889	3¼ X 10" duct. Each section 24" long. 5 sections for	12.60
890	7" round duct. Each section 24" long. 5 sections for	9.50
894	Transition Elbow with damper. Use with	
	8200-8210 for 90° turn to 3¼ X 10" duct size	3.70
895	Damper Section for 8200	2.00
	T	

5.50

5.50 1.95



Door Chimes

... a "cheerful earful" all through the house

Brilliantly designed in Contemporary and Traditional models to suit any interior. 25 handsome styles ranging from low cost two-note chimes . . to exquisite eight-note Westminster-chord masterpieces.

*NuTone "Lifetime" Finishes Will Not Rust or Tarnish



L-12 "Champion"—Plastic cover, Oyster White and Silver" or Tvory and Gold*. 2 notes front door, 1 note rear door 7½" x 4%". Weight 1 lb. 7 oz.

\$4.95 List




L-16 "Futura" — Plastic cover Oyster White and Silver* or Ivory and Gold*. 2 notes front door, 1 note rear door, 7" x 71/8" x 21/4". Weight 2 lbs.

\$7.95 List




L-17 "Decorator" — Desert Sand finish cover and brass grille. Two notes for front door, one note for rear. 47%" x 73%" x 27%". Wt. 134 lbs. \$6.95 List



L-20 "Mt. Vernon"—Gold* Antique Hammered finish Colonial design. 2 notes for front door, one note for rear door. 7" x 1134", Wt. 2½ lbs. \$10.95 List



L-21 "Rythmatic" — Walnut and Gold Anodized* or Desert Sand and Gold Anodized* Repeating Chime front door, 2 notes for rear door, one note for third door, 63%" x 75%" x 25%". Wt. 2 lbs. \$9.95 List



Prices Higher Outside Continental United States.



L-22 "Jewel"—Lime Oak or Walnut finish cover with Gold tubes. Two notes front door, 1 note for rear door. 7" x 9" x 3". Wt. 2 lbs. 3 oz. \$9.95 List



L-23 "Mayfair" — Lime Oak or Walnut finish cover with Gold* tubes. Two notes front door, 1 note rear. 7%" x 11%" x 3". Wt. 2 lbs. 2 oz. \$8.95 List



L-31 "Pacesetter"—Desert Sand finish cover. Architectural stone design grille pattern with gold flecked grille cloth. 2 notes chord tone front door, 1 note rear door 7½" x 9½" x 2½". Wt. 3 lbs. 10 oz. \$13.95 List



L-32 "Provincial" — White or Walnut and Gold* cover with antique high-lighted grille 2 notes chord tone front door, 1 note rear door. 814" x 10" x 3%". Wt. 334 lbs. \$15.95 List Walnut finish cover\$14.95 List



L-38 "Chorale" - Walnut or Desert Sand and Gold Anodized*. 8 or 4 notes front door, 1 note rear door, different note for third door. 7¾" x 14½" x 3½". Wt. 6½ lbs. Trans. included.

\$34.95 List


Use NuTone 101-0B Transformer for all 2 Note Chimes



L-39 "Golden Eight" — Lime Oak or Walnut finish cover. 8 or 4 notes front door, one note for rear door, different note for third door. 11¼" x 7¾" x 3¾" deep. Wt. 5¼ lbs. Use NuTone 301 OB Transformer. \$25.95 List




L-60 "Sunburst" — 8 or 4 chord Chime and Clock. Light Walnut or Ebony finish. Brass sunburst and bezel. 1 chord rear door, different chord third door. Transformer incl. 121/4" x 83/4" x 31/2". Wt. 10 lbs. 10 oz. \$74.95 List



L-14 "Built-In" — Ivory finish cover. May be painted to match walls. 2 notes front door, 1 note rear door. 5%" x 7%" x 13%" very deep. Cutout $4\frac{1}{2}$ " x $6\frac{1}{2}$ ". Wt. 2 lbs. \$5.95 List



L-15 "Built-In"—Silver Anodized* and White or Gold Anodized* and Ivory. 2 notes for front door, one rear. 77%" square x 2" deep. Cutout 6%" square. Wt. 2 lbs. 12 oz. \$9.95 List






Telechron Movement

L-37 Built-In "Elite" — Chord Chime and Clock. Gold, Silver or Copper Anodized*. 2 notes chord tone front door, 1 note rear door. Cover 71%" square. Box 634" sq. x 334" deep. Wt. 4 lbs. 5 oz. \$22.50 List



\$36.95 L-70



L-71 \$16.95



L-72 \$42.95

ELECTRONIC DOOR CHIME

NuTone Electronic Chimes connect with Nu-Tone Stereo-Intercom or Intercom-Radio Systems
Relay chime tones
into rooms with speakers. Have volume control. Can be heard above music or Intercom in all rooms. Even sound clearly when Stereo or Inclearly when is terred of in-tercom system is turned off. Electronic mech-anism permanently in-stalled in cabinet or housing. Transformer in cluded with each chime.

L-70 Surface Mounted "Electronic"

Adjustable for 8 or 4 notes at front door, one note rear door, different note for 3rd door. Walnut or Lime Oak finish cover — Gold Anodized Grille. 734" x 1114" x 33%".

L-71 "Electronic Built-In" L-71 "Electronic Built-In" Sounds 2 notes for the front door, one note for rear door. Gold* An-odized and Ivory. May be painted to match walls. Grille 77% sq. Cut-out6% sq. Housing 2" dp.

L-72 "Electronic **Built-In Deluxe**

Built-In Deluxe
Adjustable for 8 or 4
notes for the front door,
1 note for rear door,
different note for 3rd
door. Has Walnut finish
frame, gold flecked
grille cloth and Gold*
Anodized panel with contral knobs matches trol knobs . . . matches NuTone Stereo-Intercom system speakers. 9" wide, $10\frac{1}{2}$ " high, Cutout $7\frac{1}{6}$ " wide, $9\frac{1}{8}$ " high. Housing $3\frac{1}{6}$ " deep.



\$11.95 List



L-26 — Ivory and Gold finish cover with satin brass tubes. 2 notes front door, one note rear door. 7" x 3934" long x 3" deep.

L-33 — Walnut or Lime Oak finish cover. Three satin brass tubes. 2 notes front door, one note rear. 81/2" x 41%e" long x 2%e".

L-42—Lime Oak or Ebony finish, satin brass tubes. Selector switch for 8 or 4 notes for front door, 1 note rear, different note third door. Trans. incl. 103%" x 5" x 48½".

\$49.95 List

L-42 "Supreme"

L-56 "Jefferson" \$89.95 List

Trans. incl. 11" wide x 6" x 561/8"

Movement

L-59 "Century" \$79.95 List

Movement

L-56 — Colonial wallclock and chime with Provincial Walnut wood Selector switch for 8 or 4 notes for front door, 1 note rear, different note third door.

Wall Clock and chime. Light Walnut wood finish cover. Selector switch for 8 or 4 note for front door, 1 note rear, different note third door. Transformer included. 97%" x 51½" x 51½" long.

Use NuTone 101-OB 16 Volt Transformers for L-26 and L-33.

Models L-42, L-56, L-59, L-70, L-71 and L-72 have volume control selector switch.

PB-17 \$2.50 +PB-17L \$3.25

(LIGHTED)

PB-20 \$1.25

\$PB-20L \$1.95

(LIGHTED)

\$1.75

\$2.75 to \$5.08

For use with 16 Volt Chimes



MC-309 "Pre-Vue" Non-electric 2 Note Door Chime with Optical Lens Viewer.

Wide angle lens offers clear view of entire doorway area. Complete privacy for viewer. Gold* Anodized double window nameplate with charcoal plastic push button outside. Smartly styled Oyster White or Walnut finish cover inside. Chime cover: 156" x 31/6" x 73/6". Nameplate 34" x 23/4" x 43/6". \$7.95 List Fits all doors 3/4" to 2" thick.

MC-304 "Greeter" 2 Note Non-Electric Door Chime

Gold* or Silver* Anodized nameplate with charcoal plastic push button outside. Smartly designed Oyster White or Walnut Finish cover inside. Fits all doors 34" to 3" thick. Chime cover 13%" x 31%" x 73%". Nameplate 34" x 234" x 314". \$4.95 List With Extension Shaft, EX-311, fits door to 9" .50 List

NuTone Chimes and Transformers are Manufactured under one or more of the following U.S. Patents: 2,293,671; 2,330-439; 0-140,439; 2,408,712; 2,466,640;

2,542,947; 2,559,334; 2,659,074; 2,665,-544; 2,386,738; D180,189; D-180,406; D-180,518; 2,799,016; 2,810,123; 2,819-331. Other Patents Pending.



NUTONE LOW VOLTAGE

*ALL NUTONE TRANSFORMERS HAVE A "LIFE-TIME"
GUARANTEE—BECAUSE THEY CONTAIN A SPECIAL
BI-METAL THERMAL CUTOUT — FOR PROTECTION AGAINST OVERLOAD OR SHORT CIRCUIT"

Style 515-0B . . . 10-Volt 5 Watt . . . Powerful enough for chimes in small homes. Mounts any place. Mounting feet for open wiring. Fits any %" "knockout". Single screw bracket for quick mounting. Has thermal cutout.

U. S. Patent No. 2,819,331 \$2.75 List

Style 101-0B . . . 16 Volts (10) (VA). Mounts any place. Can take substantial surge loads. 16 volts for 2-Note Chimes also for oil and gas heating systems of air conditioning units. Has thermal cutout. U. S. Pat. 2,819,331. \$3.35 List

Style 301-0B . . . 16 Volts (30 VA) . . . Mounts any place. For use on Multiple chime installations. Can also be used for oil and gas heating systems, or air conditioning units. Has thermal cutout. \$4.52 List

Style 201-0B . . . 24 Volts (20 VA) . . . For higher loads. Mounts any place, also for oil and gas heating systems or air conditioning units. Has thermal cutout. \$4.24 List thermal cutout.

Style 320 . . . 8-16-24 Volt Trivolt . . . All purpose, low voltage Transformer with thermal cutout. Guaranteed against burnout! \$5.08 List

NuTone Transformers are U.L. Approved and CSA listed.

NuTone Sculptured Pushbuttons *NuTone Anodized Push Buttons will not rust or tarnish PB-1 \$.50 Gold* or PB-3 \$1.25 PB-11 \$.65 *PB-6L \$1.95 (LIGHTED) Gold* or Silver* Gold* or Silver* ELECTRICALLY LIGHTED PB-5 \$3.25 ‡PB-5L \$3.95 ‡PB-18 \$1.25 \$PB-10 \$1.70 \$2.50 (LIGHTED) Gold* or Silver* (LIGHTED) (LIGHTED) Gold* or Gold Silver* (LIGHTED) Gold* PR-12 \$ 42 PB-14 \$1.25 ‡PB-14L\$1.95 PB-15 \$1.25 ‡PB-15L \$1.95 PB-16 \$1.58 #PB-16L \$2.35 and Ivory (LIGHTED) Gold* (LIGHTED) (LIGHTED) Hammered Finish



t-In Stereo

Intercom - AM·FM Radio High Fidelity Music System

U.L. Listed

Now you can enjoy STEREO MUSIC throughout your entire home . . not just in a single room. You can virtually custom-build your own NuTone Stereo System to suit your own taste . . every inch of it built-in to standard (2 x 4) walls to save space and money!

Now . . A Stereo Music System All Through the House



AM-FM RADIO TUNER FOR STEREO RADIO

High Fidelity AM and FM Radio in a single chassis. Permits use of one Speaker System for an AM program, the other for an FM program, simultaneously. Also for Stereo Radio broadcasts. Solid Walnut frame. Gold anodized control and dial panels. Input plugs for auxiliary equipment. 15¾" wide, 11" high, 4" deep.

Model 2402 \$199.90



DUAL-CHANNEL AMPLIFIER COMBINED WITH INTERCOM

Two amplifiers in a single chassis, with common controls. Loudness, Balance. Treble and Bass Controls insure perfect Stereo and monaural reception. Also room-to-room Intercom. Hand-rubbed Walnut frame. Gold Anodized Control Panel. 1534" wide, 11" high, 4" deep.

Model 2401 \$228.00 Model 2401

NuTone Built-In Stereo System speakers and components cannot be used with the NuTone Intercom-Radio System.



"FOLD-AWAY" RECORD STORAGE CABINET

Matches the "Fold-Away" Record Changer. Protects up to 40 records against loss and breakage. Wired to hold tape player-recorder available soon. Walnut frame. Vinyl covered steel door. 1534" square, 4" deep. Model 2404 \$ 55.00



"FOLD-AWAY" STEREO RECORD CHANGER

Plays all speeds of Stereo and conventional records. Intermixes 10" and 12" records of the same speed. Diamond stylus for Stereo and LPs; sapphire stylus for 78 RPMs. Last record can automatically shut off entire System. Input plug for auxiliary equipment. 1534" square, 4" deep. Model 2403 \$120.00

SAVES FLOOR SPACE—AVOIDS CABINET-CLUTTER. No costly console cabinets: One set of built-in matched components uses built-in remote wall-speakers, inside and outside the home. There is a system to suit every plan and budget.

PRECISION ENGINEERED — and decorator-styled values found only in the finest electronic equipment.

A NEW 4-WAY STEREO SYSTEM

- 1. Dual-Channel Stereo Amplifier plus a room-to-room intercom.
- An AM-FM Radio Tuner to receive Stereo Radio programs.
- 3. Fold-in Wall Record Changer. Automatic shut-off and 4-speeds.
- 4. Wall Cabinet for Record Storage or Tape Deck



Built-In Coaxial Wall Speakers

The NuTone speakers are built into your walls for the finest tone. Better tone than cabinets which cannot match built-in wall enclosures for rigidity and size. Walnut frames. All-Saran, non-tarnishable grille cloth. 12%" square. Speaker with Controls: #2411 \$39.75

Speaker without Controls: #2412 \$22.00

not shown

Door Speaker #2413	\$13.00
Inside Remote Control #2416	\$29.75
Outside Remote Control #2415	\$24.75
Patio Speaker without	
Controls #2414	\$17.25
50' Wire 8 Conductor #2421	\$ 5.95
60' Wire 2 Conductor #2422	\$ 1.80
250' Wire 8 Conductor #2424	\$17.50

e See Door Chime Section for Electronic Chimes to be used with NuTone Stereo Systems.

FOR THE FIRST TIME — A Stereo AM-FM Radio-High-Fidelity Music System combined with In-tercom, — built-in — complete and ready to enjoy — not just in one room, but throughout the home, and in the Patio. Today's most wanted music — on Stereo records, in Stereo broadcasts, and on Stereo Tape. Now — all of these sensational Stereo sources — built-in.



.......

0

a home broadcasting network for your protection and pleasure

AM-FM DELUXE

Includes Master Control Station, 3 Inside Remotes, 1 Outside Remote, All wire and antennae wire.

Additional Remotes and Speakers are available (extra).

AM STANDARD

Includes Master Control Station, 3 Inside Remotes, 1 Outside Remote, All wire and antennae wire.

Additional Remotes and Speakers are available (extra).

Mutone

AM-FM DELUXE

-0 - 0 2-0

Model 2016 Copper Anodized Aluminum with Anodized Grille

AM-FM DELUXE MODEL 2015 -Satin Anodized Aluminum with Anodized Grille

Fit 4" thick wall.



SPECIFICATIONS

TUBES: Seven tubes plus Silicon Rectifier. 1-12BE6; 2-12BA6; 1-19T8; 1-ECC81/12AT7; 1-50C5 and 1-12AV6. F.M. RADIATION SPECIFICA-TIONS: Shielded to meet FCC radiation specifications. RADIO: AM broadcast range is 540 to 1650 Kilocycles. FM range is 88 to 108 Megacycles. SPEAKER: 4 x 6 oval, 3.2 OHM, Alnico V Magnet. PHONO-JACK connections. PILOT LIGHT: Two incandescent bulbs illuminate the dial and show when set is turned on. POWER CONSUMPTION: wats, 117 volts. TONE CONTROL: The tone control affects radio and phono only. Since intercom tone is critical the circuit is arranged so that it is always correct. 8 STATION SELECTOR SWITCHES.



AM STANDARD Model 2012

U.S. Pat. No. D-184.549

Baked Aluminum Enamel with Anodized Grille

AM STANDARD MODEL 2011 Baked Copper Enamel with Anodized Grille

Fit 4" thick wall.


SPECIFICATIONS

Six tubes, 1-12BE6; 2-12AV6; 1-35C5; 1-35W4. 1-12BA6, AM broadcast range 540-1650 KC. SPEAKER: 4" round, 3.2 OHM; PHONO-JACK Connections. PILOT LIGHT: Clear neon marker tells when set is on and acts as tuning marker. POWER CONSUMPTION: 30 watts 117 volts. 8 STATION SELECTOR SWITCHES.

DeLuxe and Standard Sets

Complete unit in two cartons; the "A" carton contains all roughing-in material and wire; the "B" carton contains the master chassis and the remote speaker assemblies. Either section can be bought

NuTone Intercom-Radio speakers and components cannot be used with the NuTone Built-In Stereo System.



FINEST INTERCOM FIDELITY **FULL TIME INTERCOM AUTOMATIC ACOUSTIC** LEVEL FOR INTERCOM VARIABLE CONTROLS 9 PRIMARY STATIONS AVAILABLE CHOICE OF AM and FM ONE SETTING AT MASTER

Model	Description	List
2011	AM Standard, Copper Enamel	129.50
2012	AM Standard, Aluminum Enamel	129.50
2015	AM-FM Deluxe—Satin Anodized Aluminum	179.50
2016	AM-FM Deluxe—Copper Anodized	179.50
2005	Extra Outside Remote—Gold Anodized	12.95
2020	Hi-Fidelity Accessory Speaker (Inside)	22.00
2020	Hi-Fidelity Accessory Speaker (Outside)	23.00
2024	Extra Inside Remote—Desert Sand	12.95
2040	200 Feet 3-Conductor Wire	6.75
2042	1000 Feet Reel 3-Conductor Wire	32.40

See Chime page for Electronic Chimes to be used with NuTone Stereo and NuTone Intercom Systems.



HI-FIDELITY SPEAKER . . . A high fidelity 8" coaxial speaker for the utmost enjoyment from intercom music. Use as many of these music. Use as many of these speakers as you wish—up to the maximum number of remotes possible with your intercom system. Includes rotary "Talk-Listen" and Volume Controls, and a shut-off feature for privacy. Desert Sand weather-proof housing, Gold Anodized control panel.



◆INSIDE REMOTES . . . are Desert Sand color. Can be painted to match color of wall if desired. Have variable rotary controls with privacy setting to prevent eavesdropping.

OUTSIDE REMOTES . . . Slide switch control for TWO-WAY con-versation, to and from inside re-motes or master control. Gold anodized grille weatherproof . . . Can't tarnish.





Built-In Barbecue

Electric and Charcoal Models


Model 4000 Built-In ELECTRIC Barbecue

No flavor like Barbecue . . . No Barbecue like NuTone!

For Kitchen, Family Room or any Sheltered Area "Cook-outs" . . inside the home year 'round . . rain or shine

- Channel-Grids drain grease into removable tray.
- All parts removable for easy cleaning.
- Hinged cover retains heat, saves electricity.
- Rotisserie plugs right into the unit. No cords.
- Aluminum mesh prevents scorch and flare-up.
- Dual Heat-Elements "triple-position" switch.
- Anodized Aluminum front panel keeps "New" look.

IT "DROPS-IN" TO STANDARD CABINETS . . Simply make a cutout in any standard kitchen counter . . the unit drops into place and locks in position with tension braces. Completely insulated.



Easiest to Install . . DROPS IN to standard kitchen cabinets

Built-In Barbecue Grille

No muss...no fuss...everything is neat and tidy. Brushed chrome counter rim is flush. Two-piece patented channel grids...prevent dangerous "flare-ups" by diverting the melted grease away from the blazing heat. Flavor of meat is improved because you avoid the "sooty taste."



Easy and quick to assemble. The anodized cover keeps your room cooler by preventing excess heat from escaping. Most important . . it retains and reflects the radiating heat to reduce cooking time . . saves ½ to ¾ on electricity costs of ordinary rotisseries.

U.S. and Foreign Patents Pending






Model 4000 Built-In ELECTRIC Barbecue 3200 Watts, 220 Volt.


Drop-in unit for cabinet mounting. (Fits 27" and 30" sink or range cabinets.) Fully insulated. Includes channel grids, grease receptacle, grease drip tray, aluminum grease shield, stainless steel removable side panels, 3-position switch for heat control — plug-in receptacle and fold-away support for rotisserie attachments (Model 4020).


List Price \$129.95

Model 4020 Rotisserie Attachments

Includes motor, cover, skewer and aluminum grease pan. For Model 4000. List Price \$34.95







4000 Cutout Dimensions for Counter Top Installation: 1976" wide x 1936" # 4000 Rough-in Dimensions for Masonry Installation: 1976" wide x 1917/16" long x 1416" deep

Built-In CHARCOAL Barbecue Model 4010 List price \$59.95 Has many of the same exclusive features offered in NuTone's

Has many of the same exclusive features offered in NuTone's electric model . . . WITH THE EXCEPTION THAT CHARCOAL IS USED AS THE SOURCE OF HEAT. Temperature is controlled by a heat control lever which raises and lowers the fire box.

Anodized Aluminum Front Panel with Brushed Chrome Top Plate. Includes Channel Grids, Grease Receptacle, warp-proof Fire Pan with fuel saving divider, Lift Lever for heat control, removable Stainless Aluminum panels — fold-away support for Rotisserie Attachments. 4010 not insulated) When Model 4010 is used indoors, it must be vented according to your local and national building codes.



Model 4022 INSULATION BOX \$8.95 for use with model 4010 Charcoal Barbecue


Model 4021 CHARCOAL in cabinets.

FIRE PAN For Replacement

NuTone's Model 4021 warp-resistant fire box has "easy-to-carry" handles on each side which fold down and out of the way when it is inserted in the grill.



COUNTER-TOP TRAY
Heavy anodized aluminum
with black handles . . for
serving barbecue foods.
List Price \$7.95



4010 Rough-in Dimensions for Masonry Installation: 165%" wide x 1834" long x 12½" deep — Rough-in Dimensions using # 4022 Insulation Kit: 1934" wide x 1934" long x 1234" deep





NUTONE Built-In





One Motor operates 6 Built-In Appliances

1 - Blender

Delicious frosty drinks, salads and soups. Six Speeds. Safety seated blades. Triangular shape for faster liquefying, shredding and blending.

2 - Shredder

NEW VEGETABLE SHREDDER and SLICER. For tasty salads chips and soups rich in vitamins. 3 cutting plates .. a thin slicer .. a thick slicer and a shredder.

3 - Mixer

Motor powered bowl. $3V_2$ quart size. One powerful beater mixes faster than multiple beaters. Bowl is easy to hold in one hand. All around pouring rim.

4 - Grinder

You've never tasted hamburger like this. Exclusive vertical design retains all nourishing natural meat juices. No mashing or splattering.

5 — Juicer

Enough fresh fruit juice for your entire family at one time. Holds 10 full glasses. Plastic strainer allows most nourishing pulp through — no seeds.


6 - Sharpener

Keep your knives sharp as new. Sharpens edge only without damaging blade temper. Fast and safe. Uses flexible discs . . . no hard grinding stone.

Model	Description	List Price
200	_Power Unit • Mixer • Blender • Sharpener	77.95
	Power Unit Blender	52.45 45.50
	Power Unit Only	45.50
	Blender	6.95
		3.95
	Knife Sharpener Mixing Bowl	5.95 3.95
	Meat Grinder	3.95
	Shredder-Slicer	13.95
179	Same as Model 178 minus bowl only	9.95

^{*}Fruit Juicer must be used with Mixer bowl and turntable.

NuTone's Food Center Products protected by one or more of the following U.S. Patents: D-172,127; D-172,128; D-172,129; D-177,949; D-178,854; D-180,379; 2,789,700; 2,798,345; 2,841,723; 2,868,025. Other U.S. and Foreign Patents pending.



SPECIFICATIONS

SPECIFICATIONS

1/4 horsepower motor, 340 watts, 110-120 volts AC. 6 speeds, 16,000 R.P.M. idle. Low speed drive, app. 800 R.P.M. idle. Uses tap field eliminating all complicated centrifugal switches. Stainless steel top, 50/1000" thick. Shipping weight of unit, 17½ lbs. Wiring: Provision should be made for electrical connection during rough wiring, at the proposed location of the power unit, with enough free wire to reach the front of the cabinet, when installed. Follow the Local Electrical Code for 3 amp. load. Unit must be grounded. Dimensions: Size of cut-out 45%" x 103%". Housing assembly 10" long x 4¼" wide x 6¾" high.

The only Food Preparation Center of its kind. Built into any kitchen counter top. Saves Work-Space and Saves Money

NO WASTED SPACE ...

Look at the space you save with a NuTone BUILT-IN Food Preparation Center! The recessed motor is completely out of sight to give you much more kitchen work-space. NuTone's multi-matic power drive is ready for instant use with 6 food appliances!

NO TANGLED CORDS . . .

Why clutter your kitchen with a "jungle" of plug-in cords needed for many separate food appliances? Now your counters can be smooth and tidy with the NuTone Built-in Food Center. The stainless steel surface-plate is flush and has recessed controls.

NO HEAVY LIFTING ...

Storage space is no problem with NuTone's Built-in Food Center. No need to drag heavy appliances in and out of cabinets or crowd your shelves with bulky motors. NuTone's single motor "stores itself" . . . and all attachments are light in weight!






athroom Heaters

Quick heat for bathrooms when and where needed most

See Fan Section for Home Ventilating Institute Certified Ratings




Heat-A-Vent Model 9300 Electric Wall Heater plus Exhaust Fan

Electric Wall Heater plus Exhaust Fan Electric Wall Heat PLUS Ventilation in one fixture. Saves installation cost . avoids double cutouts and double wiring. Blower has cushion-mounted motor and automatic built-in louver. Heater and fan operate at SAME TIME or separately. 2 armored heating elements . use both for 5460 BTU . or single element for 2730 BTU. Special receptacle permits optional plug-in of fan motor so that wall light switch can also control fan. Plug-in connections for fan and heating elements. Connects to standard house wire . . 117 Volts or 234 Volts three wire service, 60 cycle only.

Model 9310 with Automatic Thermostat Control

Same as Model 9300 (above) except that thermostat controls the operation of heating elements (5460 BTU). The thermostat (Double pole, Bimetal Snap Action type) has temperature range of 30° to 100° F.

Model Fin	Finish	Ventilator H.V	.I. Certified in s	quare feet	List
	Filman	Kitchen	Bath	1 Other	Price
9300	Anodized .	not used	55	75	56.95
9310	Aluminum	not used	55	75	62.95



Heat-A-Vent Lite® Models 9090-9110 Ceiling Heater plus Exhaust Fan plus Lighting

... The only Ceiling Fixture of its kind with TWO blades! Propeller for circulating warm air — Blower Wheel to exhaust odors and steam. Exhaust louver automatically closes when the circulating fan for heating is moving. Armored heating element for trouble-free operation. Flexible leads from switch assembly eliminate heavy house wire connections directly to switches. No jumper wire required. Switches are prewired at factory and mounted as one unit. New switch-wiring assembly provides for manual switch control of heater or addition of an automatic wall thermostat control unit.

Housing — 13½, diameter — 7½ deep. ½ Flange to be flush with plaster. Adjustable Mounting Brackets. Plaster ring hides edges of rough plaster or sheet rock. Spacing brackets insure correct air intake. Thermal protected to prevent over-neating.

Grille—16" diameter. Motor 60 cycle AC, 115-120 volts. Wall Switch included. Use 100 watt short bulb (not included).

Mod	el	Watts	B.T.U.	Ventilator i Kitchen	H.V.I. Certifie Bath	dinsq.ft. Other	List Price
909	0	1475	5040-5520	not used	55	75	64.95
911	0	1800	6160-6640	not used	55	75	69.95



Heat-A-Lite Model 9010

Circulating Heater plus Light


Recirculates warm air usually wasted near ceiling. Improved light pattern gives com-plete room illumination.

Grille: 16" dia. Housing $13\frac{1}{2}$ " dia. x $7\frac{1}{2}$ " deep with $\frac{1}{2}$ " flange plus adjustable mounting brackets for 0" to $\frac{3}{4}$ " plaster thickness. Extends $\frac{3}{4}$ " from ceiling.

Plaster ring hides edges of rough plaster or sheet rock. Spacing brackets on ceiling ring insure correct air intake. Thermal protected to prevent overheating

1475 watts, 5040-5520 BTU, 100 watt bulb.

U.S. Pat Nos. 2.689,906; 2.697,163; 569,322; D-166,299



Radiant Heater Model 9200 - Built-In

The perfect answer to fast, effective, safe bathroom heat. It's healthful infra-red heat spreads relaxing warmth throughout the bathroom. Specially designed arc "bounces" heat in all directions — no nearby scorches — no faraway shivers. Exclusive safety cooling system prevents fire hazard.


Housing — 13¼" dia. and 7½" deep. Reflector with outside grille 16¼" dia. 4 adjustable mounting brackets. 1000 watts, 3412 BTU. Guaranteed for one year. U. S. Patent No. 2,708,232 U.S. Pat. No. 2,708,232



Radiant Heater Model 9280 Surface mounted

Healthful infra-red heat all through the bathroom. Hugs the ceiling. Extends only 8%"
from ceiling. Mounts like a standard lighting fixture. Heats 2 ways . with DIRECT
HEAT from the element . . and with REFLECTED HEAT. Radiates heat ALL THE WAY
DOWN to the floor . . (not just limited to
upper level). upper level).

ENCLOSED, Armored Heating Element. An-odized Aluminum Reflector . . . resists cor-rosion. Guaranteed not to rust or tarnish. No extra heat bulbs or elements needed. Re-flector 1334" diameter. Ceiling plate 7" diameter. 1000 watts, 3412 BTU. Guaranteed for one year.





Radiant Heater Model 9290 SURFACE MOUNTED


A new Radiant Ceiling Heater which supplies infra-red heat all the way to the floor — not just upper levels.


Exposed parts are Anodized Aluminum. Will not rust or tarnish. Armored type heating element glows red. Surface mounts to standard junction box. Quiet motor permanent type lubricant. Grille 15" dia. Extends 3½" from ceiling. Thermal protected 1250 watts, 4265 BTU. Heats up to 375 cu. ft. Guaranteed for 1 year. U. S. and Foreign Patents Pending Pending C.S.A. Approved

BROTHER'S APPLIANCE 1016 S. FORT ST. MANDOTTE, MICH. Venue 4-3060










Electrical
Built-Ins
for
Homes











NUTONE 6000 Series "Fold-Away"® **Hood-Fans**

Matches Walls or Cabinets Color Unlimited

At last . . a range Hood-Fan to blend perfectly with the exact color of your cabinets, walls or appliances. Insert a panel of wood, metal or plastic laminate (up to 1/8" thick).

Hood-Fan folds back flush with cabinets when not in use . . and when it is opened it becomes a full sized, efficient Hood-Fan . . complete with powerful exhaust fan . . plus concealed light. Your choice of either standard or twin blower power units . . also 11 different colors and finishes of insert panels.

*The unusual features in this NuTone Hood-Fan are covered by pending U.S. and foreign patent applications and will be aggressively



Power Units Only — Combine with Hoods listed above to make one complete Hood-Fan. Includes Fan, Fan Housing, Light and Fan Dials and Light Assembly and Filter (does not include light bulbs).

Size	Model	Finish	H.V.I. Certified	List
Standard	3081	Copper Enamel Finish — Use with Copper Anodized Hoods	YES	35.95
Standard	3082	Aluminum Enamel Finish — Use with Clear Anodized Hoods	163	35.95
DeLuxe Twin	3091	Copper Enamel Finish — Use with Copper Anodized Hoods	YES	56.95
Blower	3092	Aluminum Enamel Finish — Use with Clear Anodized Hoods		56.95

Insert Panels — Hood front can match cabinets or appliances by using removable insert panels. Available in 11 colors — for use with 6015-6036 "Fold-Away" Hoods.

ı	Finish	30" Model	36" Model	42" Model	List
1	White Enamel	60100	60200	60300	2.50
9	Copper Enamel	60101	60201	60301	2.50
	Antique Copper Enamel	60103	60203	60303	3.50
1	Satin Anodized	60105	60205	60305	3.95
-	Copper Anodized	60106	60206	60306	3.95
н	Stainless Steel	60108	60208	60308	5.95
1	Turquoise Enamel	60185	60285	60385	2.50
1	Pink Enamel	60186	60286	60386	2.50
1	Yellow Enamel	60187	60287	60387	2.50
	Brown Enamel	60188	60288	60388	2.50
	Colonial Copper Enamel	60189	60289	60389	3.50

Light Kit Assembly — For use with 6000 Series Hoods listed above when used with NuTone Wall Fans. Includes Light Housing Assembly and "on-off" dials for light and fan. (Light bulbs not included).

Model 6071 Copper Enamel | Model 6072 Aluminum Enamel | 9.25



A GENTLE LIFT ... OPENS THE HOOD

A GENTLE PRESS ... CLOSES THE HOOD



protected by our company.

3000 Series Select-A-Matic* Range Hood-Fans

Deluxe Twin Blower Power Unit installed in Hood




Deluxe Power Unit installed in Hood



Standard Power Unit installed in Hood

*Select the Power Unit Select the Hood Size Select the Hood Finish Distinctive styling with "crisp" lines Three Interchangeable Power Units Prewired "plug-in" Power Units Quiet, powerful exhaust fans whisk away odors, steam, grease Recessed lighting illuminates range Power Units inside of Hood Matching Splash Plates Scallop Trim available Multiple Position Switch for Voltage variations



*Basic Models can be made up into over 140 different Hood Fan combinations



Power Units Only For use with Hoods listed above to make one complete Hood-Fan. Includes Fan, Light Assembly, Dials for Lights and Fan.

Model	Size	Finish	H.V.I. Certified	List
3061 3062	DeLuxe	Copper Enamel Alum. Enamel	Yes	51.95
3081 3082	Standard	Copper Enamel Alum, Enamel	Yes	35.95
3091 3092	DeLuxe Twin Blower	Copper Enamel Alum. Enamel	Yes	56.95

Scalloped Trim Strips — Copper RIBBED Anodized ONLY
30" 3076-30 | 36" 3076-36 | 42" 3076-42 | 48" 3076-48 | 5.50
Light Kit For use with above Hoods when used with Nutone Wall
Assembly Fans. Includes light Housing Assembly, 'on-off'' dials for
light and fan. (Light bulbs not included.) "on-off" dials for Model 6071 Copper Enamel | Model 6072 Alum. Enamel 9.25

.10 inches W. G.



Home Ventilating Institute — Certified Ratings

3400 Series Non-Ducted Hood-Fan Smoke Filter Odor Filter Grease Filter

Gets rid of GREASE, SMOKE and ODORS, the 3 major ventilation problems.

No Ductwork Needed

Hood, Motor and 3 Filter Elements come in one compact unit. Installs in minutes. Aluminum Mesh, Activated Charcoal and a special Micro-Type material purify kitchen air. Gives complete protection needed for walls and furnishings.

Grease Filter: 261 sq. in. of Aluminum Mesh traps all grease before it can leave the cooking zone.

2. Smoke Filter: Exclusive Micro-Type layer to shield the charcoal Filter and absorb sooty smoke from cooking.

3. Odor Filter: 2 lbs. of air purifying Activated Charcoal literally grabs odors before they can get away.

		Splash I 22" hi			
Size	Model	Finish	List	Model	List
30"	3410	White Enamel	84.95	SP-1710	5.50
	3411	Copper Enamel	84.95	SP-1711	5.50
	3413	Antique Copper*	87.95	SP-1713	6.50
	3415	Satin Anodized	99.95	SP-1715	13.75
	3416	Copper Anodized	99.95	SP-1716	13.75
	3418	Stainless Steel	110.95	SP-1718	20.25
36"	3420	White Enamel	87.95	SP-1720	5.95
	3421	Copper Enamel	87.95	SP-1721	5.95
	3423	Antique Copper*	90.95	SP-1723	6.95
	3425	Satin Anodized	102.95	SP-1725	15.95
	3426	Copper Anodized	102.95	SP-1726	15.95
	3428	Stainless Steel	114.95	SP-1728	24.75
42"	3430	White Enamel	89.95	SP-1730	6.50
	3431	Copper Enamel	89.95	SP-1731	6.50
	3433	Antique Copper*	92.95	SP-1733	7.50
	3435	Satin Anodized	104.95	SP-1735	18.25
	3436	Copper Anodized	104.95	SP-1736	18.25
	3438	Stainless Steel	119.95	SP-1738	27.75

See 3000 Series Hood for Matching Splash Plates *Enamel

					-	
Hood	Hood	Finish	List	Power	Power	Filter
Size	Model		Price	Unit o	or Unit	Model
30"	3010	White Enamel	19.75	3062	3092	3115
	3011	Copper Enamel	19.75	3061	3091	3116
	3013	Antique Copper*	22.75	3061	3091	3116
	3015	Satin Anodized	35.25	3062	3092	3115
	3016	Copper Anodized	35.25	3061	3091	3116
	3018	Stainless Steel	44.75	3062	3092	3115
36"	3020 3021 3023 3025 3026 3028	White Enamel Copper Enamel Antique Copper* Satin Anodized Copper Anodized Stainless Steel	21.75 21.75 24.75 37.50 37.50 49.95	3062 3061 3061 3062 3061 3062	3092 3091 3091 3092 3091 3092	3125 3126 3126 3125 3125 3126 3125
42"	3030	White Enamel	23.95	3062	3092	3135
	3031	Copper Enamel	23.95	3061	3091	3136
	3033	Antique Copper*	26.95	3061	3091	3136
	3035	Satin Anodized	39.50	3062	3092	3135
	3036	Copper Anodized	39.50	3061	3091	3136
	3038	Stainless Steel	55.25	3062	3092	3135

See 3000 Series Hood for Matching Splash Plates

U. S. Patents Pending

3100 Series Triple-Aire Kitchen Ventilating System

Kitchen Ventilation for Apartments or Remodeling No Ductwork needed Use with 3000 Series Hood and 3061, 3062, 3091 or 3092 Power Units

- Filters cooking smoke with a Micro-Flo Filter
 Avoids ozone danger to sensitive nose or throat
 Charcoal Filter shielded from grease to last longer
 Hood reaches all the way to front burners
 De Luxe Power Unit with 4 speed switch
 Attaches to cabinet, wall shelf or in soffit


Filter Units 30" - 3115; 36" - 3125; 42" - 3135 • 37.50 List Satin Anodized Aluminum

Copper Anodized Aluminum 30" - 3116; 36" - 3126; 42" - 3136 • 37.50 List

ONLY NUTONE FILTERS ALL 3!

Cooking GREASE with washable Aluminum Filter Cooking SMOKE with Micro-Flo Filter Cooking ODORS with Activated Charcoal Filter

Replacement Filters Model 842 Charcoal Odor Filter Model 843 Micro-Flo Smoke Filter



Automatic Thermal Switch

Wrap-around Filter

This Hood-Fan offers highest effective air delivery of any dual power unit in the entire ventilation field . . and yet it's super-quiet because both power units are cushion-mounted. It's the world's safast Barbecue Hood-Fan because it turns on automatically when the cooking heat goes beyond safety level, even if you forget.

5000 Series Hood-Fan

for Heavy Duty Ventilation

Offers highest effective air delivery of any dual power unit in the entire ventilation field it's superquiet because power units are cushion-mounted. It's the world's safest Barbecue Hood-Fan because it turns on automatically when the cooking heat goes beyond safety level, even if you forget.

	Units Filter,	With Hoods listed above n complete Hood-Fan. Includ Motors and two Blower V Fan and Light Switch, aut I Switch	des two Vheels,	H.V.I. Certified
	Model	Finish	List	
1	5001	Copper Enamel	83.00	Yes
	5002	Alum, Enamel	00.00	163

Hood		Combine	Match Canop 281/2"	y Kit	
Size	Model	Finish	List	Model	List
30"	5013	AntiqueCopper*	30.75	5063	22.95
	5016	Copper Anodized	43.50	5066	29.95
	5018	Stainless Steel	52.95	5068	43.95
36"	5023	Antique Copper*	32.75	5073	24.50
	5026	Copper Anodized	45.75	5076	31.50
	5028	Stainless Steel	58.25	5078	45.50
42"	5033	Antique Copper*	34.95	5083	25.95
	5036	Copper Anodized	47.75	5086	32.95
	5038	Stainless Steel	63.50	5088	46.95
5038 5043 48" 5046 5048		Antique Copper* Copper Anodized Stainless Steel	38.95 50.75 69.50	5093 5096 5098	27.50 34.50 48.50


See 3000 Series Hood for Matching Splash Plates

*Ename

Has 4-position switch to select the most suitable speed

All basic dimensions for Jet-Flo Hood-Fan and the Twin Hood-Fan are identical except for depth of hood.

1100 Series Jet-Flo Hood-Fan Factory installed Venturi fan housing attached to top of hood. Hood is prewired to outlet box. No extra wiring needed for plug-in motor. One piece motor mounting brackets. Built-in damper section — powerful pressure type fan.



	1	100 Ser	ies Jet-Flo Hood F	an	H.V.I.			
	Size	Model	Finish	List Price	Certi	Model Model	List	
10	304	1111 1113 1115	Copper Enamel Antique Copper* Satin Anodized	45.95 48.95 61.95	Yes	Splash Plates 22" high Model List SP-1711 5.50 SP-1713 6.50 SP-1715 13.75 SP-1723 6.95 SP-1723 6.95 SP-1723 6.95 SP-1733 7.50 SP-1733 7.50 SP-1735 18.25 Includes Hood, Fan and Built-in damper and Filter Splash Spla		
	36"	1121 1123 1125	Copper Enamel Antique Copper* Satin Anodized	48.25 51.25 63.95	Yes	SP-1723	6.95 15.95	
	42"	1131 1133 1135	Copper Enamel Antique Copper Satin Anodized	49.95 52.95 66.50	Yes	SP-1733 7.50		
			1500 Twin Hood-F	an				
	36"	1521 1525 1526	Copper Enamel Satin Anodized Copper Anodized	62.95 81.25 81.25	Yes	Fan and Built-in	damper	
	42"	1531 1535 1536	Copper Enamel Satin Anodized Copper Anodized	64.95 84.25 84.25	Yes	and Filt	er	

*Enamel

"Fold-away" Oven Hood-Fan Series

Does not disturb baking temperatures 101/2 101/2 but not more than 221/5"

Fits flush with cabinet when not in use. Fan automatically starts when Hood is pulled to "open" position. Protects cabinets from heat, grease and smoke which escape from built-in oven when door is opened. Filter and Fan easily cleaned. Includes, Filter and Fan

Size	Description	Model	List
24"	Antique Copper Enamel Stainless Steel	3203 3208	17.45
27"	Antique Copper Enamel Stainless Steel	3213 3218	17.45
32"	Antique Copper Enamel Stainless Steel	3223 3228	17.45
	Unit • Fits above Hoods to omplete Oven Hood-Fan	32 60	34.50

See back page for Ventilation Accessories





for a fresh, clean odor-free kitchen

U.L. Listed and C.S.A. Approved










Pull Chain Wall Fan

10"

Installs in wood or brick walls. Sturdy venturi housing for greater air delivery at reduced noise level. Has weather-tight shutter outside the house with 13¾" square wall plate. The housing, "snap-in" motor and blade assembly, and grille are packed in one carton. One piece grille installs with single thumb screw. Has easy to install "plug-in" motor.

Model No.	Blade Size	Grille Fi and Si		Wall Thickness		V.I. CERTII n square fo Bath		List Price
8000 8020 8040 8010 8030 8050 8110 8130	8" 8" 8" 8" 8" 10"	White White White Anod. Alum. Anod. Alum. Anod. Alum. Anod. Alum. Anod. Alum.	11" Sq. 13½" Sq. 13½" Sq.	9" To 141/8" 35/8" To 61/4" 5" To 101/8" 9" To 141/8" 35/8" To 61/4" 5" To 101/8"	125 125 125 125 125 125 125 250 250	Over 200 Over 200 Over 200 Over 200 Over 200 Over 200 Over 200 Over 200	325 325 325 325 325 325 0ver 500 Over 500	26.95 26.95 26.95 27.95 27.95 27.95 36.25 36.25

Note: 8" Models fit 91/8" dia. wall opening. 10" Models fit 111/8" dia. wall











8110 - 8130

Automatic Wall Fans

10"


Installs in wood or brick walls. Sturdy venturi housing for greater air delivery at reduced noise level. Automatic weather protecting hood with patented* flutter proof shutter. 1334" sq. wall plate is outside the house. "Snap-in motor and blade assembly, and grille packed in one carton. One piece grille installs with single thumb screw. Has "plug-in" motor.

* U. S. Pat. No. 2,800,853

Model No.	Blade Size	Grille Finish and Size		Wall Thickness		I. CERTIF square fe Bath		List Price
8060 8080	8"	White 11"	Sq.	5" To 10" 9" To 14"	80 80	150 150	200 200	26.95 26.95
8070 8090	8" 8"	Anod, Alum. 11"	Sq.	5" To 10" 9" To 14"	80 80	150 150	200 200	27.95 27.95
8170 8190	10" 10"	Anod. Alum. 131/2	Sq.	5" To 10" 9" To 14"	125 125	Over 200 Over 200	325 325	36.25 36.25

NOTE: 8" Models fit 91/8" dia. wall opening. 10" Models fit 111/8" dia. wall opening.

8" Models use Model 834 Filter. 10" Models use Model 854 Filter. 8" Models use Model 861 Three Speed Switch. 10" Models use 860 Three Speed Switch.
























Ceiling or Inside Wall Fans


Venturi housing for greater air delivery at reduced noise level is $3\frac{1}{4}$ deep, fits 2" x 4" construction. Has "snap-in" motor and pressure type blade assembly. Fits standard $3\frac{1}{4}$ " x 10" duct. Mounts between 16" C.C.* joists or studding. Housing, motor and blade assembly and grille packed in one carton. One piece grille installs with single thumb screw. Has easy to install "plug-in" motor.


Mo	odel	Blade Size	Grille Finish and Size		H.V.I. CERTIFIED in square feet		
		Size		Kitchen	Bath	Other	Price
	310 510		Anod. Alum. — 11" dia. Anod. Alum. — 13½" dia.	80 150	150 Over 200	200 375	27.95 36.95

NOTE: 8" Fan uses Model 834 Filter (extra). 10" Fan uses Model 854 Filter (extra).

Both Fans use Model 860 Three Speed Switch (extra).

Model 8310 includes hanger bars.





Vertical Discharge Fans

10"


Installs in ceiling for ventilating to the roof. "Snap-in"* motor and blade assembly with hanger bars (included) installs between 16" C.C. joists. Housing, motor and blade assembly and grille packed in one carton. One piece grille installs with single thumb screw. Has easy to install "plug-in" motor. Anodized Grilles Guaranteed

* Model 8220 has motor mounting bracket with keyhole slots.

Model	Size	Filter (extra)	Grille Size	Ceiling Opening	Duct Size	H.V.I. CERTIFIED in square feet Kitchen Bath Other		List Price	
8200 8210 8220 8490	8"	# 834 # 834 # 834 # 854	11" dia. 11" dia. 10½" sq. 13½" dia.	91/8" dia. 91/8" dia. 91/8" dia. 11" dia.	7" dia. 8" dia.	125 100 80 125	Over 200 185 150 Over 200	325 250 200 325	22.95 23.95 20.95 32.75

NOTE: Model 8210 includes built-in damper. Model 8490 includes builtin reducer with damper

Model 895 Damper Section for Model 8200 available (extra). Fits 7" diameter duct.





1100 SERIES NJF "B" UNIT

INSTALLATION INSTRUCTIONS

- 1. Loosen the mounting screws located in tabs inside fan housing. Place large end of keyhole slot in bracket over the screws and lock bracket into place. Tighten screws firmly. Plug motor into receptacle. Fig. 1.
- 2. Place mounting hole in name plate of grille over stud in motor bracket. Fasten grille firmly in place with thumb nut furnished. Fig. 2.




FIG. 1



Mutone, Inc

FACTORY AND NATIONAL HEADQUARTERS
MADISON AND RED BANK ROADS
CINCINNATI 27, OHIO

6893

INC., Madison and Red Bank Roads, Cincinnati 27, Ohio CINCINNATI 27, OHIO

MIDWEST SALES Old Orchard Arcade, Skokie, Illinois, (suburb of Chicago) NORTHWEST SALES WESTERN SALES NORTH CALIFORNIA 4003 Empire State Building, 350 5th Ave., New York 1 SOUTHWEST SALES 820 North Harwood St., Dallas 1 408 Ninth Ave. North, Seattle 9 308 11th St., San Francisco 3

6230 Chambord St., Montreal, Quebec, Canada

CANADIAN SALES

